



SAFETY DATA SHEET

Page : 1

Revised edition no : 1

Date : 4 / 8 / 2008

Supersedes : 0 / 0 / 0

BRISTOL - BRUSHING FILLER

4012000600

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name : BRISTOL - BRUSHING FILLER
Description : Spirit based paint
Type of product : Paint.
Identification of the product : Liquid.
Use : Primer and filler for new wood
Domestic.
Industrial.
Company identification : Bristol Coatings Holland
Stationsweg 13
2675 AM Honselersdijk NETHERLANDS
0031-(0)174-629006
www.bristolcoatingsholland.nl
Emergency phone nr : 0031-(0)30-2748888 (24 hours, NVIC, only contact in the event of accidental poisoning by treating doctor)

2 HAZARDS IDENTIFICATION

Risk Phrases : This product is flammable.
Environmental hazard : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Primary route of exposure : Vapours inhalation.
Repeated or prolonged skin contact.
Symptoms relating to use
- Inhalation : Vapours may cause drowsiness and dizziness.
- Skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.
- Eye contact : Contact with the eyes is likely to be irritating.
- Ingestion : May cause lung damage if swallowed.
Must not come into contact with food or be consumed.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Components : This product is hazardous.

Substance name	Contents	CAS No	EC No	Annex No	Classification
Naphta heavy (low boiling point hydrogen treated)	10 - 25 %	64742-82-1	265-185-4	649-330-00-2	R10 Xn; R65 R66 R67 N; R51-53
Xylene	< 1 %	1330-20-7	215-535-7	601-022-00-9	R10 Xn; R20/21 Xi; R38
2-butanone oxime	< 1 %	96-29-7	202-496-6	616-014-00-0	Carc. Cat. 3; R40 Xn; R20 Xi; R41 R43
Naphta heavy (low boiling point hydrogen treated)	< 1 %	64742-48-9	265-150-3	649-327-00-6	Xn; R65 R66
Ethylbenzene	< 1 %	100-41-4	202-849-4	601-023-00-4	F; R11 Xn; R20

4 FIRST AID MEASURES

First aid measures
- General information : Allow the victim to rest.
In case of loss of conscience place the victim in the recovery position.
Never give anything by mouth to an unconscious person.
Seek medical attention if ill effect develops.



SAFETY DATA SHEET

Page : 2

Revised edition no : 1

Date : 4 / 8 / 2008

Supersedes : 0 / 0 / 0

BRISTOL - BRUSHING FILLER

4012000600

4 FIRST AID MEASURES (continued)

- Inhalation : Assure fresh air breathing.
Keep victim warm and rested.
If you feel unwell, seek medical advice (show the label where possible).
If not breathing, give artificial respiration.
- Skin contact : Wash skin with mild soap and water.
Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- Eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.
Seek medical advice.
- Ingestion : If swallowed, rinse mouth with water (only if the person is conscious).
Do not induce vomiting.
If swallowed, seek medical advice immediately and show this container or label.

5 FIRE-FIGHTING MEASURES

- Flammable class : This product is flammable.
- Specific hazards : May form flammable/explosive vapour-air mixture.
Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.
- Prevention : Keep away from sources of ignition.
No smoking.
- Extinguishing media : Dry powder.
Foam.
Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.
- Surrounding fires : Use water spray or fog for cooling exposed containers.
- Protection against fire : Do not enter fire area without proper protective equipment, including respiratory protection.
- Special procedures : Exercise caution when fighting any chemical fire.
Avoid (reject) fire-fighting water to enter environment.

6 ACCIDENTAL RELEASE MEASURES

- Special precautions : This product contains : Solvent.
- Personal precautions : Use recommended respiratory protection. No smoking.
- General precautions : Eliminate every possible source of ignition.
No naked lights. No smoking.
Do not breathe dust.
- Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.
- Clean up methods : Clean up any spills as soon as possible, using an absorbent material to collect it.
Use suitable disposal containers.

7 HANDLING AND STORAGE

- Precautions in handling and storage : May form flammable/explosive vapour-air mixture.
Good ventilation of the workplace required.
Keep away from sources of ignition - No smoking.
Handle in accordance with good industrial hygiene and safety procedures.
- Personal protection : Avoid contact with skin and eyes.
- Technical protective measures : Use only non-sparking tools.
Ground well.
- Storage : Store in dry, well-ventilated area.
Keep away from sources of ignition.
Keep away from food, drink and animal feeding stuffs.

BRISTOL - BRUSHING FILLER

4012000600

7 HANDLING AND STORAGE (continued)

Storage - away from	Keep in fireproof place. Close container tightly after use.
Handling	: Oxidizer. Strong bases. Heat sources. Direct sunlight. Strong acids. : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection



- Respiratory protection	: Suitable respiratory equipment.
- Hand protection	: Use rubber gloves.
- Skin protection	: Wear suitable protective clothing.
- Eye protection	: Chemical goggles or safety glasses.
- Ingestion	: When using, do not eat, drink or smoke.
Industrial hygiene	: Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations.
Occupational Exposure Limits	: Xylene : ILV (EU) - 8 H - [mg/m³] : 221 (Skin.) Xylene : ILV (EU) - 8 H - [ppm] : 50 (Skin.) Xylene : ILV (EU) - 15 min - [mg/m³] : 442 (Skin.) Xylene : ILV (EU) - 15 min - [ppm] : 100 (Skin.) Ethylbenzene : ILV (EU) - 8 H - [mg/m³] : (442 Skin.) Ethylbenzene : ILV (EU) - 8 H - [ppm] : (100 Skin.) Ethylbenzene : ILV (EU) - 15 min - [mg/m³] : (884 Skin.) Ethylbenzene : ILV (EU) - 15 min - [ppm] : (200 Skin.) 2-(2-butoxyethoxy)ethanol : ILV (EU) - 8 H - [mg/m³] : 67.5 2-(2-butoxyethoxy)ethanol : ILV (EU) - 15 min - [mg/m³] : 101.2 2-(2-butoxyethoxy)ethanol : ILV (EU) - 8 H - [ppm] : 10 2-(2-butoxyethoxy)ethanol : ILV (EU) - 15 min - [ppm] : 15

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C	: Viscous liquid.
Colour	: White.
Odour	: Aromatic.
Solubility in water	: Insoluble.
Flash point [°C]	: 41°C

10 STABILITY AND REACTIVITY

Stability and reactivity	: Stable under normal conditions.
Hazardous decomposition products	: Thermal decomposition generates : Carbon monoxide. Carbon dioxide. Nitrogen oxides. When heated to decomposition, emits dangerous fumes.
Hazardous properties	: May form flammable/explosive vapour-air mixture.
Materials to avoid	: Strong acids. Strong bases. Oxidizer.



SAFETY DATA SHEET

Page : 4

Revised edition no : 1

Date : 4 / 8 / 2008

Supersedes : 0 / 0 / 0

BRISTOL - BRUSHING FILLER

4012000600

10 STABILITY AND REACTIVITY (continued)

Conditions to avoid : Open flame.
Heat.

11 TOXICOLOGICAL INFORMATION

On product : No data available.
- Dermal : Prolonged or repeated contact may cause skin to become dry or cracked.
- Ocular : Risk of damage to eyes.
- Ingestion : Symptoms of ingestion include drowsiness, weakness, headache, dizziness, nausea, vomiting.

12 ECOLOGICAL INFORMATION

Ecological effects information : Avoid release to the environment.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

General : Avoid release to the environment.
Dispose of this material and its container at hazardous or special waste collection point.
Dispose in a safe manner in accordance with local/national regulations.

14 TRANSPORT INFORMATION

In packages of up to 450 liters exempt from ADR according ADR 2.2.3.1.5. If > 450 liters applies:

Proper shipping name : UN1263 PAINT, 3, III
UN No. : 1263
H.I. nr : 30
Land transport
ADR/RID : Group : III
Class : 3
Special provision : 640E
- ADR/RID Classification code : F1
Labelling ADR

}

Sea transport
- IMO-IMDG code : 1263
- Class : 3.3
- IMO Packing group : III
- EMS-Nr : 3-05
- MFAG-Nr : 330
- IMDG-Marine pollution : Yes.
Air transport
- ICAO/IATA : Class 3
- IATA Packing group : III
- IATA-Label : Flammable liquid.



SAFETY DATA SHEET

Page : 5

Revised edition no : 1

Date : 4 / 8 / 2008

Supersedes : 0 / 0 / 0

BRISTOL - BRUSHING FILLER

4012000600

15 REGULATORY INFORMATION

Symbol(s)	: None.
R Phrase(s)	: R10 : Flammable. R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66 : Repeated exposure may cause skin dryness or cracking. R67 : Vapours may cause drowsiness and dizziness.
S Phrase(s)	: S2 : Keep out of the reach of children. S23 : Do not breathe spray. S46 : If swallowed seek medical advice immediately and show this container or label. S51 : Use only in well-ventilated areas.
Further Phrases	: Contains : 2-butanone oxime. May produce an allergic reaction.
VOC (Volatile organic compounds) g/l	: EU limit value for this product(cat.A/d): 400 g/l (2007) / 300 g/l (2010) This product contains max 300 g/l VOC.

16 OTHER INFORMATION

Text of R-Phrases in § 3	: R10 : Flammable. R11 : Highly flammable. R20 : Harmful by inhalation. R20/21 : Harmful by inhalation and in contact with skin. R38 : Irritating to skin. R40 : Limited evidence of a carcinogenic effect. R41 : Risk of serious damage to eyes. R43 : May cause sensitization by skin contact. R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 : Harmful : may cause lung damage if swallowed. R66 : Repeated exposure may cause skin dryness or cracking. R67 : Vapours may cause drowsiness and dizziness.
--------------------------	--

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document